


SS-240NM-A(ISO)LED

“ * ”

" "	AUX 12V (:H)	0-10V/PWM/Resistor	()		
BH		✓			
BHB	✓	✓	✓		
BHP	✓	✓		✓	

--	--	--	--	--

	180V		260V	
	200V		260V	Po=Vo*Io=240W
	0.92A		1.2A	1.2A 200V 0.92A 260V
AOC	0.84A		1.2A	
			/	

--

		8
		%
	PWM	8
	PWM	7
	PWM	K
	PWM	6
		K
		0
	≤ 85	
MTB		220Vac, , 25 (
		85
		34mm

25

--	--	--	--	--

Tcase	-40	25	+90	
	-40	25	+90	
	10%RH		90%RH	
	5%RH		95%RH	
	-65m		4000m	

(ISO) LED


UL		
2U+1000Vac		
2U+1000Vac		
2U+1000Vac		
500Vac		
≥ 10MΩ		500Vdc
≤ 0.1Ω	25A/1min	
≤ 0.75mA	347Vac	

MC

EN


L/N

/



Vs.


/AOC



----- Dimming Window


————— AOC Window

Vs. (Vin=220Vac)




Vs. (Vin=347Vac)

Power Factor



--- Vin=220Vac --- Vin=347Vac

Vs.




--- Vin=220Vac --- Vin=347Vac


SS-240NM-A(ISO)

LED


Vs.



Vs.



Vs.





1

2

AC

DC

10±2mm;

LED

DIM

/

/

:

:

!

:

:

:

:

SS-240NM-A(ISO) LED



1		,		,		704
2						υ
		<				
3	“	”	“	50	”	c c 380cm²
	115cm³;	(		LED		c
4						
5		LED+	LED-			
6						
7	LED	≈	÷			
8	LED			D		
9			LED			
10	η		Ω			


LED			(	
(				

-		mm	×	×	=495 × 385 × 162;
-		16			
-	0.65kg			11.9kg	
-					

--	--	--	--	--	--

		GB 3873	83
1			

RoHS					
RoHS	(2011/65/EU)			2015/863/EU	



V00		2026/07/27	