





输入性能：






输出性能(SS-40PA-57F):

	19V		57V	19-38V
	38V		57V	Po=Vo*Io=40W
	0.7A		1.05A	1.05A 38V,0.7A 57V
AOC	0.3A		1.05A	
			63V	

调光特性：



		10%loset		loset	

其他性能：

--	--	--	--	--

--	--

	≤ 75	≥ 100,000 hours	80%
	MTBF	250,000 hours	230Vac, , 25 (MIL-HDBK-217F)
		IP20	
		90	
		8	75
		535g	
		134mm*77mm*37mm	x x

环境要求：

Tcase	-40	25	+90	
	-40	25	+90	
	10%RH		90%RH	
	5%RH		95%RH	
	-65m		4000m	


安规与电磁兼容标准：

ENEC	EN 61347-1:2015+A1:2021 EN 61347-2-13:2014+A1:2017 EN IEC 62384:2020	✓	
UKCA	EN 61347-1:2015/A1:2021 EN 61347-2-13:2014/A1:2017 EN 62493:2015/A1:2022	✓	
EAC	EN 61347-2-13:2014+A1:2017 EN61347-1:2015+A1:2021	✓	
CE	EN 61347-1:2015/A1:2021 EN 61347-2-13:2014/A1:2017 EN 62493:2015/A1:2022	✓	

EMI/EMS	/	
	EN IEC 55015:2019/A11:2020	
	EN IEC 55015:2019/A11:2020	
	EN IEC 61000-3-2:2019/A1:2021	Class C
	IEC/EN61000-4-5	B 8kV 6kV
	EN61547:2009	B 10kV 6kV


安规测试项目：

特性曲线：




特性曲线：

Vs. (/AOC)



特性曲线：

Vs. (Vin=230Vac)



特性曲线(SS-40PA-57F):


特性曲线(SS-40PA-133F):

特性曲线：

Vs.

Vs.





40W NFC

DALI-2 & D4i





变更履历表

--	--	--	--

V00 W 024 / 01/ 12		2024/01/12	

