



--	--	--	--	--	--


--	--	--



	100Vac		277Vac	
	90Vac		305Vac	
	47Hz		63Hz	
			5.8A	100Vac

(120Vac)			60A	
(220Vac)			110A	冷机启动
(277Vac)			140A	冷机启动
			0.5W	220Vac/60Hz ,
	0.95	0.98		220Vac/50Hz , 满载
	0.90			100-277Vac/50Hz , 70-100%载
		8%	10%	220Vac/50Hz , 满载
			20%	100-277Vac/50Hz , 70-100%载














Vs. (Vin=220Vac)



Vs. (Vin=277Vac)




Vs.



SS-480CA LED

Vs. (50)



Case Temperature () 70 75 80 85 90 95 100

Vs.

Vs.

SJOW 3*17AWG, :8.0mm :L, :N, :⏏

DC (**300±10mm**)

SJTW 2*18AWG :7.3mm :V+ :V-
H05RN-F 2*1.0mm² :6.8mm :V+ :V-
SJOW 2*17AWG, :7.7mm :V+, :V-

DIM (**220±10mm**)

/ / UL 21996 4*22AWG 5.6mm DIM+
:DIM- / :Vaux+ / :Vaux-

DALI (**220±10mm**)

/ / UL 21996 4*22AWG 5
:DA / :Vaux+ / :Vaux-

		mm(In.)
PG	A	M12*1.5
	4-B	Φ8.5(0.33)
	D	Φ208.0(8.19)
	H	69.5(2.74)
	Z	M20*2.5(17mm) G1/2(17mm)
	R	M4*0.7
	W	192.0(7.56)

Tc	X	50(1.97)
Tc	Y	25(0.98)







V00		2020/05/20	

