




SS-200GA-E

LED

	100Vac	220-240Vac	305Vac	
	47Hz	50/60Hz	63Hz	
			1.4A	220Vac
			220W	
			75A	
			7.5W	220Vac/50Hz 0
	0.95	0.97		
	0.90			
		8%	10%	
			20%	

(SS-200GA-E62*)

	40V		62V	Po=Vo*Io=200W
	3.2A		5.0A	5.0A 40V,3.2A 62V
AOC	0.7A		5.0A	
			80V	
	90.0%	92.0%		62V/3.2A

			+5%	
PK-AV		5%	10%	
			10%	


(SS-200GA-E286*)

(SS-200GA-E378*)

	286V		378V	Po=Vo*Io=200W
	0.53A		0.7A	0.7A 286V,0.53A 378V
AOC	0.1A		0.7A	
			450V	

--	--	--	--






ðˆ—e÷j! v@ ß! —e÷ 8 Ð k C' Ð V € íòˆ—e÷ÿ € ß# —e÷]î 9 òˆ—e÷j! v@ ß! —e÷ 6 Ð k C' Ð V € íòˆ—e÷ÿ é ViÂ—UhRV

1.

EMC

EMC
2.


LN



		T(@10%)	T(@50%)
220Vac	75A	750uS	300uS


(SS-200GA-E62*)

Vs. (/AOC)




----- Dimming Window ————— AOC Window

Vs. (Vin=220Vac)



----- Io=5000mA - - - - Io=3200mA




SS-200GA-E LED

(SS-200GA-E378*)

Vs.

_____ Vin=220Vac

Vs.



_____ Vin=220Vac



SS-

^{*}
A



S



☒ 启用

B(10.00

0.0 %

0V 8.00







-

mm

×

×

=495 × 385 × 162;

-

16


-

0.74kg

13.38kg

-

3.. × Ě Ě



V00			2025/06/11	